



OAK SORRENTO

The natural variations in the timber used in this 3-strip oak floor from the Sand Collection are enhanced by a soft white finish, resulting in an elegant and light expression. The matt lacquer finish eliminates glare while protecting the wood from daily wear.

PRODUCT DETAILS

Product type / Construction	Wood Flooring / 3-layer parquet
Article Number / EAN Code	153N38EK0VKW240 / 7393969027229
Design / Wood Species	3-strip / Oak
Surface treatment / Natural/Stained	Matt lacquer / Stained
Width x Length x Thickness	200 x 2423 x 15 mm
Weight per package / per m2	23 kg / 7.93 kg
Area per package / per pallet	2.9 m ² / 130.1 m ²
Grading	Variation
Joint	Woodloc® 5S
Installation method	Floating, Glue-down
Floor heating	Yes
Wear leayer material / thickness	Hardwood / 3.5 mm
Resandable	2-3 times
Core material	Pine/Spruce lamella
Hardness (Brinell) value / range	3,7 / 2.2 - 5.9
LRV / LRV Std1	37 / 3.2

PRODUCT DETAILS

Warranty	30 years	
TECHNICAL PROPERTIES		
Moisture content	EN13183	7%±2%
Minimun Mean Density	>500 kg/m³	
kg/m³		
Reaction To Fire	EN13501-1	Dfl-s1
Formaldehyde Emission	EN717-1	E1
Content PCP	CEN/TR14823	≤ 5 ppm
Breaking Strength N/mm²	EN1533	NPD
Thermal Conductivity	EN12664	0,11W/mK
Thermal Resistance R-Value	.11 (m2K/W)	
Biological Durability	EN350-2	Class 1
CARB2	Compliant	
Slip resistance	CEN/TS15676	NPD



DETAILED DESCRIPTION

Even colour with minor variations.
Small sized knots in limited numbers allowed.
Colour change: Stained product - noticable color change over time.
Packages may contain start and stop boards.

Descriptions & Imagery

Other products in this collection



Oak Amalfi



Oak Rügen



Oak Norderney



Oak Estoril



Oak Sorrento



Oak Portofino



Oak Brighton



Ash Skagen



Ash Sandvig



Ash Falsterbo